

C-401 C-401-B ペダルタップ



仕 様

適合サイズ	C-401	BC9/16×20山
	C-401-B	BC1/2×20山
重量	170g	
全長	120mm	

■ 左右1組

ご使用上のご注意

本製品は、ペダルのネジ山を修正するためのタップです。
この目的以外に使用しないでください。

⚠ 注意

1. 本器は精密な切削工具です。取り扱いには十分注意してください。投げたり落としたりすると、タップの破損や故障の原因となります。
2. 割れ、欠け、磨耗、変形などが認められる場合は使用しないでください。
3. ご使用の際は必ず切削油をご使用ください。

ご使用方法

- 1 本体の刻印をご確認ください。
RH…右側ペダルに使用します。
LH…左側ペダルに使用します。
- 2 シャンク四角部の幅が9mm対応のタップ
ハンドルを掛けてタップを回転します。

⚠ 注意

RHは正ネジ、LHは逆ネジを表しています。

⚠ 注意

1. ネジ山はテーパ状となっています。一気に切り進めず、実際にペダルを取り付けて様子を見ながら作業を行ってください。
2. 作業の際は必ず切削油をご使用ください。

長くお使いいただくために

- タップはご使用後、直ちに切り粉などを除去し、衝撃を与えないよう保管してください。

ホーサン株式会社

本社 〒556-0021 大阪市浪速区幸町1-2-12

製品・補修部品はWebサイトにてご購入いただけます。

<https://www.hozan.co.jp/>



技術的なお問い合わせ

ホーサン テクニカルホットライン

☎06-6567-3132

E-mail : th@hozan.co.jp

【月曜日から金曜日（祝日を除く）の
10:30～12:00、13:00～17:00】

C-401 C-401-B PEDAL TAP



Specifications

Applicable bottom bracket	C-401	BC9/16×20
	C-401-B	BC1/2×20
Weight	170g	
O.A.L.	120mm	

■ Right and left.

Precautions

These taps are for correcting the threads on bicycle pedals.
Do not use for any other purpose.

⚠ Caution

1. Be careful in handling, since these are precision cutting tools. Do not drop or throw down. This could damage these taps.
2. Do not use when cracks, breaks, excessive wear or deformation is found on this tap.
3. Always apply cutting oil when use.

Operation

- 1 Check stamps on the bodies.
RH...Use for the right pedal.
LH...Use for the left pedal.
- 2 Use a tap handle on the market which corresponds to the square portion of the shank of 9 mm for turning these taps.

⚠ Caution

RH means the right screw.
LH means the reverse screw.

⚠ Caution

1. Do not cut all at once since the threads are tapered. Work gradually checking the fitting to the pedal.
2. Always apply cutting oil when use.

Daily care

Remove the cut scrap from taps after use. Store avoiding shocks.

HOZAN CO., LTD.

1-2-12 Saiwaicho, Naniwa-ku, Osaka 556-0021, Japan
https://www.hozan.co.jp/cycle_e/ E-mail: th@hozan.co.jp