

HOZAN C-402

ハンガータップ



製品情報

仕様

適合ハンガーサイズ	BC1.37×24山(JIS)
重量	1020g
全長	105mm
材質	SK3

■ 左右1組

ご使用上のご注意

本製品は、BB (ボトムブラケット) のネジ山修正用タップです。
この目的以外に使用しないでください。

⚠ 注意

1. 本器は精密な切削工具です。取り扱いには十分注意してください。投げたり落したりすると、タップの破損や故障の原因となります。
2. 割れ、欠け、磨耗、変形などが認められる場合は使用しないでください。

ご使用方法

- 1 本体の刻印をご確認ください。
RH…左ハンガーに使用します。
LH…右ハンガーに使用します。

⚠ 注意

1. RHは正ネジ、LHは逆ネジを表しています。
2. 1 3/8-24の表記がありますが、BC1.37×24山用で間違いありません。ご了承ください。

- 2 シャンク四角部の幅が20mm以上対応のタップハンドルをかけてタップを回転します。

⚠ 注意

回転方法にはくれぐれもご注意ください。左ハンガーは作業者から見て時計方向、右ハンガーは反時計方向となります。

長くお使いいただくために

- タップはご使用後、直ちに切り粉などを除去し、衝撃を与えないよう保管してください。
- 錆防止のため、定期的に潤滑油などをしみ込ませたウエスでふいて保管してください。

ホーサン株式会社

本社 〒556-0021 大阪市浪速区幸町1-2-12

製品・補修部品はWebサイトにてご購入いただけます。
<https://www.hozan.co.jp/>



技術的なお問い合わせ

ホーサン テクニカルホットライン

☎06-6567-3132 / E-mail : th@hozan.co.jp

【月曜日から金曜日(祝日を除く)の10:30~12:00、13:00~17:00】

HOZAN C-402

BOTTOM BRACKET TAP



INSTRUCTION MANUAL

Specifications

Applicable bottom bracket	BC1.37×24 (JIS)
Weight	1020g
O.A.L.	105mm
Material	SK3 (JIS) Carbon tool steel

■ Right and left.

Precautions

These taps are for correcting the threads on a bicycle bottom bracket. Do not use for any other purpose.

⚠ Caution

1. Be careful in handling, since these are precision cutting tools. Do not drop or throw down. This could damage these taps.
2. Do not use when cracks, breaks, excessive wear or deformation is found on this tap.

Operation

- 1 Check stamps on the bodies.
RH...Use for the left bracket.
LH...Use for the right bracket.

⚠ Caution

1. The tap stamped "RH" is for right screw and "LH" is for reverse screw.
2. These are correctly for BC1.37×24 regardless of the indication "1 3/8-24".

- 2 Use a tap handle on the market which corresponds to the square portion of the shank of 20 mm or more for turning these taps.

⚠ Caution

Be careful in turning direction. Turn the tap driver clockwise for the left bracket and counter-clockwise for the right bracket to the operator.

Daily care

- Remove the cut scrap from taps after use. Store avoiding shocks.
- Lubricate periodically with an oiled cloth to prevent rusting.

HOZAN CO., LTD.

1-2-12 Saiwaicho, Naniwa-ku, Osaka 556-0021, Japan
https://www.hozan.co.jp/cycle_e/ E-mail: th@hozan.co.jp